

Foam Extinguisher

- Kitemarked to BS EN3
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base*
- Complete with bracket
- 6ltr & 9 ltr have passed the 35kv conductivity discharge test

*Excludes 2ltr model



Stored Pressure

Spray foam extinguishers provide a fast, powerful means of tackling flammable liquids. The foam forms a seal over the surface to prevent re-ignition. Ideal for multi-risk usage and safe to use in close proximity to electrical equipment.

| Type | AFFF Foam Spray S/P | AFFF Foam Spray S/P | AFFF Foam Spray S/P | AFFF Foam Spray C/O |
|------------------------------|---------------------|---------------------|---------------------|---------------------|
| Capacity (ltr) | 2 | 3 | 6 | 9 |
| Fire rating | 8A 55B | 13A 89B | 13A 144B | 21A 183B |
| Height (mm) | 395 | 435 | 565 | 600 |
| Cylinder diameter (mm) | 112 | 130 | 160 | 189 |
| Overall width (mm) | 150 | 290 | 290 | 300 |
| Filled weight (kg) | 3.81 | 5.55 | 10.09 | 14.21 |
| Range of throw (m) | >2 | >2 | >4 | >4 |
| Duration of discharge (secs) | 12 | 18 | 30 | 40 |
| Working pressure (at 20°C) | 15 bar | 15 bar | 15 bar | 15 bar |
| Temperature range (°C) | 0 to 60 | 0 to 60 | 0 to 60 | 0 to 60 |
| BS EN3 approved | yes | yes | yes | yes |
| MED approved | | | yes | yes |