

## Foam Extinguisher

- Kitemarked to BS EN3
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base\*
- Complete with wall bracket
- 3ltr, 6ltr & 9ltr have passed the 35kv conductivity discharge test

\*Excludes 2ltr model



Stored Pressure

Spray foam extinguishers provide a fast, powerful means of tackling flammable liquids. The foam forms a seal over the surface to prevent re-ignition. Ideal for multi-risk usage and safe to use in close proximity to electrical equipment.

Type	AFFF FOAM SP	AFFF FOAM SP	AFFF FOAM SP	AFFF FOAM SP
<b>Capacity (Kg / Ltr)</b>	<b>2</b>	<b>3</b>	<b>6</b>	<b>9</b>
Fire rating	8A 55B	13A 89B	21A 144B	27A 183B
Height (mm)	395	426	560	522
Cylinder diameter (mm)	112	130	150	190
Overall width (mm)	150	300	300	340
Filled weight (kg)	3.81	5.3	9.65	13.24
Range of throw (m)	>2	>4	>4	>4
Duration of discharge (secs)	12	18	30	50
Working pressure (at 20°C)	15 bar	15 bar	15 bar	15 bar
Temperature range (°C)	+5 to +60°C	+5 to +60°C	+5 to +60°C	+5 to +60°C
BS EN3 approved	yes	yes	yes	yes
MED approved	no	no	no	yes
Part Number	9204/00	9233/00	9234/00	9235/00
Model Number	FPF2	FPRF3	FPRF6	FPRF9
Rating Symbol	A B	A B	A B	A B