

Powder Extinguisher

- Kitemarked to BS EN3
- Multi-purpose application
- Squeeze grip operation
- Corrosion resistant finish
- Protective plastic base*
- Complete with bracket

*Excludes 1kg and 2kg models



Stored Pressure

Dry Powder is a highly versatile medium for tackling most types of fires. Extremely effective on electrical hazards, flammable liquids and gases, which makes this ideal for vehicle fires.

Type	ABC Powder SP	ABC Powder SP	ABC Powder SP	ABC Powder SP	ABC Powder SP	Monnex Powder SP
Capacity (Kg / Ltr)	1	2	4	6	9	9
Fire rating	8A 55B	13A 70B	21A 113B	34A 233B	43A 233B	233B
Height (mm)	340	370	420	503	588	620
Cylinder diameter (mm)	80	112	150	150	170	190
Overall width (mm)	135	150	293	260	317	310
Filled weight (kg)	1.67	3.62	6.4	8.94	12.98	14.4
Range of throw (m)	>2	>2	>6	>6	>7	>7
Duration of discharge (secs)	9	10	16	20	20	20
Working pressure (at 20°C)	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar
Temperature range (°C)	-30 to +60°C	-30 to +60°C	-30 to +60°C	-30 to +60°C	-30 to +60°C	-20 to +60°C
BS EN3 approved	yes	yes	yes	yes	yes	yes
MED approved	no	no	no	yes	yes	no
Part Number	9315/00	9307/00	9318/00	9319/00	9320/00	9324/00
Model Number	FPP1	FPP2	FPRP4	FPRP6	FPRP9	FPRP9M
Rating Symbol	A B C E	A B C E	A B C E	A B C E	A B C E	A B C E