

Monitored Input/Output Fire Alarm Interface



The 6000/MICCO is Protec's loop powered, fault monitored input/output fire alarm interface

Standards / Approvals

- EN 54-17, EN 54-18
- UKCA
- CE

Technical Specification

Product Code	6000/MICCO
Environment	-10°C to +50°C (95% R.H. non condensing)
Ingress Protection	IP20
Weight	109g
Din Rail Mounted	No
Inputs	1 x Monitored Input
Outputs	1 x Clean Contact Output
Isolator	Yes, on board (consult Protec DEL2110 for details)
Compatible Panels	6500, 6100, 6400, 6300
Number of Loop Addresses Used	1
Loop Alarm Current (Average)	2.2 mA
Loop Alarm Current (Peak)	5 mA
Loop Protocol	6000/6000PLUS
Loop Powered	Yes
Loop Voltage Range	16 V dc - 28 V dc peak loop
Loop Quiescent Current (24V Loop Peak)	0.55 mA
Zone Quiescent Current	n/a
Zone Reset Time	n/a
Max Number of Detectors	n/a
Detectors Supported	n/a
Sounders Supported	n/a
Clean Contact Output Details	Single pole changeover rated for 8 A at maximum 30 V dc non inductive
Dimensions (mm)	147.3(W) x 86.7(H) x 10(D)
Technical Documentation	DEL2109

Data within this document are subject to change without notice.

Protec Fire and Security Group Ltd. Protec House, Churchill Way, Nelson, BB9 6RT
www.protec.co.uk | sales@protec.co.uk | support.protec.co.uk | +44 1282 717171