

DATA INFORMATION NOTICE IN ACCORDANCE WITH REGULATION (EU) 2023/2854 (‘DATA ACT’) FOR CONNECTED PRODUCTS

PROTEC’S DETECTOR RANGE (“PRODUCT”)

Connected products and related services of Protec Fire & Security Group Limited generate various data and information during their use. Below you will find information on the product data generated by the Product, data access and your data rights.

1. TYPE, FORMAT AND ESTIMATED VOLUME OF PRODUCT DATA

The following product data may be generated during operation and use of the Product. The actual data generated varies depending on the specific use of the Product.

1.1 Types of product data

- (a) Physical data: Environment data (e.g. temperature, pressure, power, energy)
- (b) Device identification data (e.g. serial number, hardware and software version)
- (c) Status data (e.g. on/off, present/not present)
- (d) Error messages
- (e) Setting values / user configurations (e.g. room setpoint temperature, time programmes)
- (f) [Diagnosis Data (e.g. voltage data, working hours, pollution levels, etc.)]

1.2 Estimated volume

The estimated volume of product data varies depending on the data point and the use of the Product, with data volumes per data point ranging 250 KiB/h – 10 MiB/h.

1.3 Data format

The product data is stored within the Product in various data formats and, as part of a data export, is provided at least in the following data format: XML, TXT, JSON

1.4 Currentness of product data

The product data in the Product is generated [during use and operation in real time and continuously; at different intervals depending on the type of data property. Intervals range from 15min to once every 24h..

2. STORAGE LOCATION AND STORAGE DURATION

The product data is stored in the Product

3. ACCESS MODALITIES

Direct product data access is available at the USB interface of the panel.

4. TECHNICAL MEANS AND REQUIREMENTS FOR DATA ACCESS:

- (a) A computer with associated software and data cable
- (b) Individual usage requirements

5. TERMS

Users and third parties are prohibited from using or providing data received to derive insights about IP, know-how, technical implementations, the economic situation, assets and production methods of Bosch and its affiliates. The provision of data to other parties may only take place based on strict confidentiality obligations and technical access restrictions in order to protect legitimate interests of Bosch and its affiliates.

6. LIST OF ANNEXES

The following Annexes form an integral part of this notice:

Annex	Content
64-460-70-X + 64-462-72-X	Beam Detector, 140 to 160 Metre Range
64-460-70-X	Beam Detector, 7 to 70 Metre Range
64-460-70-X + 64-461-71-X	Beam Detector, 70 to 140 Metre Range
64-277-73-IS	Convectonal Intrinsically Safe Heat Detector
SP10842	Convectonal Intrinsically Safe Smoke Detector
SP11827	Heat Detector 54-70 Degrees
SP20002	Standard Sensor Base for the PFD/EVC-H-A2 Heat Detector
SP7336	Detector Protective Polycarbonate Stopper
SP7087	Detector Protective Steel Web Stopper for Surface Wiring
65-600-68	Detector Protective Steel Web Stopper for Flush Wiring
SP2831	Intrinsically Safe Standard Mounting Base For IS Detectors
6000/WLS/HT	Intelligent Wireless Heat Detector Complete with Base and Batteries
6000/WLS/OP	Intelligent Wireless Optical Smoke Detector Complete with Base and Batteries
6000/WLS/OPHT	Intelligent Wireless Multi Criteria Detector Complete with Base and Batteries
AFX-0001	13 METRE 360 DUAL TECHNOLOGY DETECTOR - PREMIER ELITE AM360DT
DT8016AF24	16 X 22 MTRE DUAL TECH DETECTOR
IS3016A-1	16 X 22 METRE INTELLISENSE PIR DETECTOR WITH AM
PFD/CO4A-2230-EU	Wireless CO Detector (Batteries Included)
64-262-66	Weatherproof Heat Detector (Suitable For Abattoirs, Chillers & Freezers)
TMD15G3	15 METRE TMD DUAL TECHNOLOGY DETECTOR - (TWIN TEC)
PFD/AFB-0053	PROTEC BRANDED PREMIER ELITE 15 MTRE DUAL TECHNOLOGY DETECTOR

SP3269	Laser Focus Aspirating Fire Detector (VLF-250-00)
SP4414	Laser Focus Aspirating Fire Detector (VLF-500-00)
SP0576	Laser Industrial Aspirating Fire Detector (VLI-880) Relays & Ethernet
SP2994	Laser Scanner Aspirating Fire Detector, 4 Zones c/w Programmer, Display & 12 Relay's
SP10842	SOC-E-IS CONVENTIONAL OPTICAL I.S. DETECTOR
64-277-73-IS	DCD-1E-IS CONVENTIONAL HEAT I.S. DETECTOR
61-986-HRDP	Aspirating Detector Remote Display Programmer (ADRDP)