6000PLUS Optical Smoke and Heat Sensor inc. Sounder



The 6000PLUS/OPHT/S is Protec's digital addressable, point type, optical heat multi-sensor with integrated sounder

Standards / Approvals

- EN 54-3, EN 54-5, EN 54-7, EN 54-17
- UKCA
- CE

Technical Specification

Product Code	6000PLUS/OPHT/S
Environment	-10°C to +50°C (95% R.H. non condensing)
Ingress Protection	IP41
Weight	105g
Loop Powered	Yes
Loop Standby Load	0.4mA
Loop Alarm Load (Average)	6.0mA
Loop Voltage	18-28V
Maximum Sounder Output Levels (Configured at Panel)	High 85dB (A), Mid 75 dB(A), Low 65dB(A)
VAD Flash Rate	n/a
Mounting	Surface or recessed
Material	ABS to UL94-V0 flammability rating
Isolator	Yes
Cutout	n/a
Dimensions (mm)	98.60Ø x 49(H)
Technical Documentation	DEL2222

Data within this document is subject to change without notice.
Protec Fire and Security Group Ltd. Protec House, Churchill Way, Nelson, BB9 6RT
www.protec.co.uk | sales@protec.co.uk | support.protec.co.uk | +44 (0)370 9071710